

SETHNESS PRODUCTS COMPANY

ADDITION OF CARAMEL COLOR IN A NON-AQUEOUS (FAT) SYSTEM

Our recommendations for anyone trying to disperse Caramel Color in a non-aqueous (fat) system are the following procedures:

Suggestion 1:

1. Disperse any powdered or liquid Caramel Color in an equal weight of propylene glycol or glycerol. The dispersion will look like a paste; it can be thinned down by increasing the percentage of propylene glycol or glycerol.
2. Disperse this mixture into the fat phase by using high shear mixing and a small amount of a nonionic surfactant such as Polysorbate 80 or Polysorbate 20 (less than 0.5%).

Suggestion 2:

1. Disperse any powdered or liquid Caramel Color into lecithin.
2. Disperse this mixture into the fat phase by using high shear mixing and a small amount of a nonionic surfactant such as Polysorbate 80 or Polysorbate 20 (less than 0.5%).

Suggestion 3:

1. If the application contains a fondant blend, add the powdered or liquid Caramel Color to this material.
2. Mix this fondant/Caramel Color blend in the (fat) phase by high shear mixing.

Using one of the above techniques, a customer should be able to achieve a relatively stable emulsion of Caramel Color in a non-aqueous (fat) system.

FAT SYSTEM APPL 004/LAB/APPLICATIONS	PAGE 1 OF 1	Authorized by JME
1347 Beaver Channel Parkway, Clinton, IA 52732	Original: 04/04/13	Revised: 11/02/18

NOTE: Once this document is copied, printed, emailed, downloaded, or modified in any way from what is stated on its' docsign sheet, it becomes UNCONTROLLED. For the current Controlled Document or assistance contact lab@sethness.com or www.sethness.com or call 888-772-1880.